

technical data sheet






EN

Product specifications

Multi-Ply Oak wood flooring	EN 14342 (Free Class)	DOP PQ2021-1
Dimensions	Plank	625 x 125 x 15/ 3 mm
	Box	16 planks / 1,25 m ² / 11,50 kg
	Nested lengths	-
	Pallet	64 boxes / 80 m ² / 756 kg
Density	EN ISO 23996	600-650 kg/m ³
Installation	ISO 24334	T&G (glued)
Top layer		3 mm Asian oak (Quercus Mongolica)
Grading		Rustic B+
Surface		Distressed, scraped and brushed
Bevel		Aged bevel 4V
Gloss level	60°	5-9%
Finishing		UV oil (Pure), OX oil (others)
Warranty conditions	Residential use	20 years
	Commercial use	upon request
Application	EN 14342	Class 23



Product properties

Property	Test method	min. req.	result
Indoor air certifications			A, REACH
Fire resistance	 EN 13501-1		Dfl-S1
Slip resistance	 EN 13893		DS (≥ 0.30)
Formaldehyde emission	 EN 717-1	≤ 0.124 mg/m ³	E1
Pentachlorofenol content	 EN 12673	< 5 ppm	< detectable limit
Underfloor heating	 EN 12667	R < 0.15 m ² K/W	R = 0,12 m ² K/W OK (max +28°C) + glued
Biological durability			Class 1

Cleaning and maintenance instructions: www.lamett.eu



Rustiek B+

EN

Grading description

Texture	Hand scraped and brushed — Bevel: Distressed
Grading	Very rustic
Colour variation	High
Sound knots	Allowed unlimited
Unsound knots	Allowed unlimited
Bark	Allowed unlimited
Sapwood	Allowed unlimited
End crack	Allowed unlimited
Surface crack	Allowed unlimited
Insect hole	< 3mm; 8/400mm partially filled
Decay	Not allowed
Blue/yellow stain	Allowed
Sound heart	Allowed
Machine marks	Not allowed



This picture is an indication of the grading as described.

Grading description — 2 criteria

Knots

Scale from (rigid) parquet without knots up to planks with more and larger knots



Colour variation

Scale from (rigid) parquet without knots up to planks with more and larger knots

